



Product Specifications

SRW Commercial Silt Fence

| | |
|-----------------|---|
| Roll Dimensions | 2' x 50', 2' x 100', 3' x 100', or 3' x 1500 fabric only |
| Stakes | 7 or 13 stake (2' rolls); 13 or 26 (3' rolls) |

| Physical Properties | Test Method | Results |
|---------------------|-------------|---------|
| Weight (typical) | ASTM D-3766 | 2.1 |
| Grab Tensile (lbs) | ASTM D-4632 | 65 |
| Grab Elongation (%) | ASTM D-4632 | 18% |
| Puncture (lbs) | ASTM D-4833 | 40 lbs |
| UV Resistance (%) | ASTM D-4355 | 80% |

| Hydraulic Properties | Test Method | Results |
|------------------------------|-------------|---------|
| AOS, US Sieve Number | ASTM D-4751 | 40 |
| Permittivity gal/min sq. ft. | ASTM D-4491 | .1 |

Characteristics

| | |
|-------------------|--------------------|
| Yarn Construction | Polypropylene Tape |
| Color | Black |

| | |
|--------------------|--|
| Wood Stakes | 2" x 2" x 48" (nominal) hardwood 1 1/2" x 1 1/2" x 48" (actual) |
|--------------------|--|

Stakes are available separately in 30, 42 and 48".